



PHONE: (949) 299 7261
Email: info@conceptrender.com

THIS IS AN ORIGINAL UNPUBLISHED WORK
AND MAY NOT BE REPRODUCED, DUPLICATED
PUBLISHED OR OTHERWISE USED IN WHOLE
OR PART WITHOUT CONSENT OF
CONCEPT DESIGN GROUP

RESIDENTIAL DUPLEXES
728 W. VASSAR AVE.
FRESNO CA

SITE PLAN


Revisions

Project #:
Date:
Drawn :
Checked:

Sheet Number

A1.0

GENERAL NOTES



VICINITY MAP
NOT TO SCALE

| | |
|--------|--------------------------------|
| A1.0 | GENERAL INFORMATION, SITE PLAN |
| A1.1 | CAL GREEN |
| A2.0 | FLOOR PLAN |
| A3.0 | ELEVATIONS |
| A4.0 | SECTIONS |
| AD-1 | DETAILS |
| AD-2 | DETAILS |
| AD-3 | DETAILS |
| S-1.0 | FOUNDATION PLAN |
| S-2.0 | ROOF FRAMING PLAN |
| S-3.0 | LATERAL PLAN |
| SD-1 | STRUCTURAL DETAILS |
| SD-2 | STRUCTURAL DETAILS |
| SD-2.1 | STRUCTURAL DETAILS |
| SD-3 | STRUCTURAL DETAILS |
| SD-4 | STRUCTURAL DETAILS |
| SD-5 | STRUCTURAL DETAILS |
| SD-6 | STRUCTURAL DETAILS |
| E-1.0 | ELECTRICAL PLAN |
| M-1.0 | MECHANICAL PLAN |
| M-2.0 | ENERGY COMPLIANCE (T-24) |
| P-1 | PLUMBING PLAN |
| P-2 | HOT WATER AND GAS PLAN |
| FP1-3 | FIRE SPRINKLER PLANS |
| PV-1 | SOLAR COVER SHEET |
| PV-2-5 | SOLAR PLANS |
| | SOLAR DETAILS |
| GP.0 | GRADING PLAN AND DETAILS |

- ALL WORKS TO COMPLY WITH THE 2019 CALIFORNIA RESIDENTIAL CODE (CRC)
- ALL WORKS SHALL BE COMPLETED BY THE END OF THE WORKS BEFORE STARTING WORK. THE CONTRACTOR SHALL NOTIFY THE OWNER OR THE ARCHITECT IMMEDIATELY IF ANY DISCREPANCIES ARE FOUND.
- DRAWING ORGANIZATION: THE ORGANIZATION OF THESE DRAWINGS IS NOT INTENDED TO CORRECT THE DESIGN OF WORK OR TO PROVIDE A BASIS FOR THE OWNER'S OR CONTRACTOR'S CLAIMS.
- ENTRY DOORS MUST BE PROVIDED WITH A PEEP HOLE OR VISION PANEL, STEEL PLATE AT THE DEAD-BOLT STRIKER, SOLID SHM 6" ABOVE AND BELOW WITH TWO #8 x 7 SCREWS. PROVIDE DEAD BOLT AT ALL EXTERIOR DOORS.
- ALL EXTERIOR DOORS SHALL BE PROVIDED WITH A LOCKING MECHANISM, KEYS AND WINDS TO MEET MINIMUM STANDARDS PER CRC SECTION 8600.
- PROVIDE SUFFICIENT NUMBER OF INSULATION MARKERS IN ATTIC.
- AFTER THE INSULATION IS INSTALLED, THE INSTALLER SHALL PLACE IN A CONSPICUOUS LOCATION IN THE BUILDING, AN "INSULATION CERTIFICATE" SIGNED BY THE INSTALLER AND THE BUILDER STATING THAT THE INSULATION CONFORMS WITH THE REQUIREMENTS OF TITLE 24.
- ALL EXTERIOR WEATHER SEALING AND SEALING OF EXTERIOR DOORS, WINDOWS AND BUILDING ENVELOPE OPENINGS, AS REQUIRED BY THE STANDARDS SHALL BE SUBJECT TO FIELD INSPECTION.
- THE CEILING OR FLOOR ACCESS SHALL BE WEATHER-STRIPPED AND INSULATED TO THE EQUIVALENT OF THE CEILING OR FLOOR JOINTS. ACCESS SHALL BE SECURED BY A LOCKING MECHANISM. A LOCKING MECHANISM ATTACHED USING ADHESIVE OR MECHANICAL FASTENERS, THE ATTIC ACCESS SHALL BE GASKETED TO PREVENT AIR LEAKAGE.
- ALL EXTERIOR DOORS, WINDOWS, PANELS AND EXTERIOR WALL SHALL BE PROTECTED BY AN APPROVED NON-REMOVABLE TIE-BACK-FLOOR PREVENTION DEVICE.
- SHOWER HEADS AND FAUCETS SHALL BE CERTIFIED TO THE PERFORMANCE CRITERIA FOR SHOWERHEADS IN COMPLIANCE WITH THE 2019 CALIFORNIA RESIDENTIAL CODE (CRC) SECTION 408.3.
- BUILDER SHALL PROVIDE THE ORIGINAL ORIGINATOR, WITH A LIST OF HEATING, COOLING, WATER HEATING, LIGHTING AND SOLAR DEVICES INSTALLED IN THE BUILDING, TO THE APPLICANT, AT THE TIME OF THE PERMITS APPLICATION.
- PERMITS SHALL BE PROVIDED WITH A FINISH FINAL INSPECTION, AN APPLICANT CERTIFICATE PROVIDED BY THE APPLIANCE MANUFACTURER MUST BE COMPLETED BY THE INSTALLER OR GENERAL CONTRACTOR AND POSTED IN A CONSPICUOUS LOCATION.
- PERMITS SHALL BE PROVIDED WITH A FINISH FINAL INSPECTION, AN APPLICANT CERTIFICATE PROVIDED BY THE APPLIANCE MANUFACTURER MUST BE COMPLETED BY THE INSTALLER OR GENERAL CONTRACTOR AND POSTED IN A CONSPICUOUS LOCATION.
- WHEN PROVIDED BY THE CONTRACTOR, SPECIFY THE INSTALLATION OF THE CERTIFIED APPLIANCE AND EQUIPMENT:
 - a) REFRIGERATOR/FREEZER
 - c) GAS SPACE HEATER
 - e) PLUMBING FITTINGS
 - f) CENTRAL AIR CONDITIONING
 - g) WATER HEATER
 - h) FLOURESCENT LAMP BALLASTS
- CHANGING TOILET REQUIRED ON-SITE DURING CONSTRUCTION
- AIR CONDITIONING EQUIPMENT DESIGNED TO BE IN A FIXED POSITION SHALL BE SECURELY FASTENED
- FASTENERS, INCLUDING NAILS AND WASHERS, FOR PRESERVATIVE-TREATED & FIRE-RETARDANT-TREATED WOOD SHALL BE OF HOT DIP GALVANIZED STEEL (ASTM A 153), STAINLESS STEEL (ASTM F1554), SILICON BRONZE (ASTM B 16) OR ALUMINUM FASTENERS (ASTM B 29). GALVANIZED STEEL SHALL BE COATED WITH MECHANICALLY DEPOSITED ZINC-COATED STEEL WITH COATING WEIGHTS IN ACCORDANCE WITH ASTM B695, CLASS 55 MM. (CRC SECTION 803.2.3)
- END-JOINTED LUMBER (FINGER JOINTED STUDS) IDENTIFIED BY A GRADE MARK SHALL BE PERMITTED TO BE USED INTERCHANGEABLY WITH SAWN-SAWN MEMBERS OF THE SAME SPECIES AND GRADE (CRC 8606.2.1.2)
- ALL EXTERIOR STRUCTURES, INCLUDING BUT NOT LIMITED TO, PORCHES, PATIOS, DECKS, ETC., SHALL BE INSTALLED IN CONSTRUCTION SUBJECT TO TITLE 24. PART 8 SHALL HAVE ATTACHED TO IT A CLEARLY VISIBLE THERMAL PROPERTY LABEL OR HAVE AN ADJUSTABLE LABEL CERTIFICATE THAT LISTS THE U-FACTOR, THE SOLAR HEAT GAIN COEFFICIENT (SHGC) OR THE U-FACTOR AND R-VALUE TO REFLECT THOSE VALUES, AND CERTIFIES COMPLIANCE WITH AIR LEAKAGE REQUIREMENTS OF THE CALIFORNIA ENERGY CODE, SECTION 116(4). THE LABEL SHALL NOT BE REMOVED UNTIL THE END OF THE BUILDING CONSTRUCTION.
- EMERGENCY ESCAPE AND RESCUE OPENINGS SHALL HAVE THE BOTTOM OF THE CLEAR OPENING NOT GREATER THAN 44" MEASURED FROM THE FLOOR. (CRC 310.2.2). MINIMUM OPENING AREA SHALL BE NOT LESS THAN 24" NET CLEAR HEIGHT AND NOT LESS THAN 20" NET CLEAR WIDTH. THE TOP OF THE CLEAR OPENING SHALL BE NOT LESS THAN 66" NET CLEAR HEIGHT AND NOT LESS THAN 20" NET CLEAR WIDTH. NET CLEAR OPENING SHALL HAVE NET CLEAR OPENING OF NOT LESS THAN 5 SQUARE FEET. (CRC 310.3.2.1)
- EGRESS DOOR: NOT LESS THAN ONE EGRESS DOOR SHALL BE PROVIDED FOR EACH DWELLING UNIT. THE EGRESS DOOR SHALL BE OF SOLID MATERIAL, NOT LESS THAN 1 1/2" THICK, AND SHALL BE PROVIDED WITH A LOCKING MECHANISM AND THE TOP OF THE DOOR OPEN NO GREATER. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE NOT LESS THAN 44" MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE LANDING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. THE CLEAR HEIGHT OF THE DOOR OPENING SHALL BE NOT LESS THAN 80 INCHES IN HEIGHT MEASURED FROM THE TOP OF THE THRESHOLD TO THE BOTTOM OF THE STEP. EGRESS DOORS SHALL BE READILY OPENABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE. (CRC 803.2.1.2)
- IF THERE IS A LANDING OR FLOOR ON EACH SIDE OF EACH EXTERIOR DOOR, THE WIDTH OF EACH LANDING SHALL BE

STANDARD PLAN

| | | | | |
|--|-----------------|--------|-----------------------------------|-----------------------------|
| | AREA | SQ.FT. | FIRE SPRINKLER STANDARD PLAN # | BUILDING STANDARD PLAN # |
| | GROSS | 3,327 | | |
| | LIVING UNIT 101 | 1,226 | | |
| | LIVING UNIT 102 | 1,226 | | |
| | 2 CAR GARAGE | 533 | 0 | 0 |
| | PORCH | 157 | | |
| | COVERED PATIO | 185 | | |

SITE NOTES

- 1 THESE PLANS AND RELATED DOCUMENTS MUST BE AVAILABLE AT THE JOB-SITE DURING ANY INSPECTION ACTIVITY.
- 2 BUILDINGS SHALL BE PROVIDED WITH APPROVED IDENTIFICATION. THE ADDRESS IDENTIFICATION SHALL BE LEGIBLE AND
3 PLACED AT THE POINT OF ENTRY TO THE PROPERTY FROM THE STREET OR ROAD FRONTING THE PROPERTY ADDRESS.
4 IDENTIFICATION CHARACTERS SHALL CONTRAST WITH THEIR BACKGROUND. EACH CHARACTER SHALL BE NOT LESS THAN 4
5 INCHES HIGH, 1 INCH WIDE, AND COME WITHIN 60% OF NOT LESS THAN 0.5 INCH. ADDRESS IDENTIFICATION SHALL BE
6 MAINTAINED. (CPRC 2019 R16.16)
- 7 CONTRACTOR MUST ADJUST PLACEMENT OF RESIDENCE IF NECESSARY AS LONG AS ALL MINIMUM SETBACKS ARE
8 MAINTAINED.
- 9 PROJECTS LOCATED IN THE FLOOD HAZARD AREA SHALL HAVE A FINISHED FLOOR ELEVATION OF AT LEAST ONE
10 INCH ABOVE THE 100 YEAR FLOOD LEVEL.
- 11 NO DRAINAGE TO ADJACENT PROPERTY.
- 12 NO ON-SITE WATER RETENTION.
- 13 ALL DRAINAGE TO STREET SHALL BE ONE-HALF PERCENT (0.5%) SLOPE SUFFICIENT TO FLOW WATER FROM FRONT TO
14 REAR.
- 15 PROVIDE A 5% SLOPE FOR A MINIMUM DISTANCE OF 10' FROM THE BUILDING
- 16 NO PORTION OF THE DRIVEWAY SHALL EXCEED A GRADE 18%.
- 17 **APR 2020 6 INCH LOTS SHALL BE GRADDED TO DRAIN SURFACE WATER AWAY FROM FOUNDATION WALLS. THE GRADE SHALL
18 NOT FEWER THAN 6 INCHES WITHIN THE GRASSY TO 1 FEET EXCEED WHERE LOT LINES, SLOPES PROHIBIT 6 INCHES OF FLOW WITHIN 10 FEET
19 OF THE BUILDING FOUNDATION. THE GRADE SHALL BE GRADUALLY SLOPED FROM THE BUILDING TO THE STREET SURFACES WITHIN 10 FEET
20 OF THE BUILDING FOUNDATION. THE GRADE SHALL BE SLOPED NOT LESS THAN 2% AWAY FROM THE BUILDING. SHOULD THERE BE A SIGNIFICANT
21 "POCKET," A CERTIFIED GRADING PLAN WILL BE REQUIRED TO BE SUBMITTED BY A REGISTERED CIVIL ENGINEER.**
- 22 ALL DRAINING OUTSIDE OF THE BUILDING ENVELOPE IS REQUIRED TO BE A MINIMUM OF .5% DIRECTED TOWARDS
23 THE STREET.
- 24 TYPICAL DRAINAGE, FINISH GRADE SECTIONS, AND FINISH FLOOR ELEVATIONS PER TRACT SEE CIVIL DRAWINGS SHEET
25 C1.
- 26 THE AS-GRADDED PLAN MUST BE APPROVED PRIOR TO ISSUANCE OF PERMITS FOR THIS TRACT
- 27 THIS PROJECT DOES INCORPORATE LANDSCAPING IN CONFORMANCE TO THE "MUELLO" REQUIREMENTS PER CALIFORNIA
28 CODE OF REGULATIONS, TITLE 23, CHAPTER 27, DIVISION 2. REFER TO LANDSCAPE PLAN FOR DESIGN AND
29 INSTALLATION REQUIREMENTS.
- 30 AT THE TIME OF FINAL INSPECTION, THE PERMIT APPLICANT MUST PROVIDE THE OWNER OF THE PROPERTY WITH A
31 CERTIFICATE OF COMPLETION, DATE OF INSTALLATION, LANDSCAPE, LANDSCAPE AND IRRIGATION
32 MAINTENANCE.
- 33 CONSTRUCTION WASTE MANAGEMENT PLAN MUST BE FINALIZED PRIOR TO OCCUPANCY.
- 34 A STATE OF CALIFORNIA FLOOD ELEVATION CERTIFICATE OF COMPLIANCE ZONE TWO ELEVATION
35 CERTIFICATION AREA REQUIRED IT BE PROVIDED TO THE INSPECTOR, THE FIRST IS REQUIRED TO ACQUIRE AT THE FOUNDATION
36 INSPECTION AND THE SECOND IS REQUIRED AT THE FINAL INSPECTION. 2019 CPRC R16.1

FIRE NOTES


| | |
|---|--|
| 2 | MULTIPURPOSE FIRE SPRINKLER SYSTEM TO BE INSTALLED |
| 3 | OBTAIN FIRE SPRINKLER FINAL INSPECTION APPROVAL PRIOR TO BUILDING FINAL |
| 4 | ALL INTERIOR WALL COVERINGS: CLASS II FLAME SPREAD |
| 4 | PROVIDE FIRE BLOCCING VERTICALLY AT THE CEILING AND FLOOR LEVELS, HORIZONTALLY AT INTERVALS NOT EXCEEDING (10) TEN FEET. (C.R.302.11) |
| 5 | THE PERMIT FOR THIS PROJECT REQUIRES FIRE SPRINKLERS (C.R.313.2). LAYOUT AND DETAILS OF THE FIRE SPRINKLER SYSTEM SHALL BE DESIGNED IN ACCORDANCE WITH NEPA 100 OR C.R. SECTION R303.3, REVISED AND SHALL BE APPROVED BY THE APPLICABLE FIRE MARSHAL PRIOR TO PERMITTING THE PLANS. THE FIRE SPRINKLER SYSTEM SHALL BE INSTALLED BY A LICENSED FIRE SPRINKLER CONTRACTOR OR OWNER-OCCUPIED OWNER BUILDERS, AND SHALL BE INSPECTED AND APPROVED BY THE APPROPRIATE FIRE MARSHAL PRIOR TO APPROVAL OF OCCUPANCY OF THE BUILDING. |

PROJECT DATA

| | | | |
|---------------------------------------|---|---|-------------------|
| OWNER, CONTRACTOR, PREPARED BY: | Chodhroallah Hognarast (559) 860 9035 Keyvan Abedi (559) 288 7178 Email: hognarast@yahoo.com kinnusa@yahoo.com | CODE EDITIONS: 2019 CRC, CEC, CMC, CPC, CFC 2019 CAL. ENERGY CODE 2019 CAL. GREEN CODE | |
| STRUCTURAL ENGINEER: | ENGINEERING DESIGNS HAYAT A. MOHAMMAD, P.E. 5155 NORTH FIRST STREET FRESNO, CA 93711 PHONE: (559) 225-2525 | OCCUPANCY GROUP RESIDENCE: GARAGE: TYPE OF CONSTRUCTION: | R-3 VB |
| NO. OF STORIES | Single Story Duplexes | | |
| A.P.N. | 44404118 | | |


CONSULTANTS

| | |
|--|--|
| CIVIL ENGINEER: | FIRE SPRINKLER ENGINEER: HSI Fire Sprinkler (661)474 4482 5511 W Sierra Madre Dr. Bakersfield, 93313 CA |
| TRUSS MANUFACTURER: CV TRUSS 10715 E American Ave, Del Rey, CA 93616. (559)888 2160. | LANDSCAPE DESIGNER: |
| MECHANICAL DESIGNER: Juvie Martinez (559) 696 7922 juvieenergysolutions.com | SOLAR DESIGNER: Solar Maintenance Pros (559)3553544 4175 W Sierra Madre #103 Fresno, CA 93722 |



SITE PLAN

SCALE = 1"=10'-0"



FLOOR PLAN

SCALE = 1/4"=1'-0"

FENESTRATION VALUES

| TYPE | U-VALUE | SHGC | CLEAR | W/GRIDS | MATERIAL | NOTES |
|----------------|---------|------|-------|---------|----------|------------|
| SINGLE HUNG | 0.30 | 0.23 | 0.20 | | VINYL | SH |
| PICTURE WINDOW | 0.30 | 0.25 | 0.23 | | VINYL | PW |
| SLIDING WINDOW | 0.30 | 0.23 | 0.21 | | VINYL | XO |
| SLIDING DOOR | 0.30 | 0.23 | 0.21 | | VINYL | SLD. TEMP. |

INSULATION SCHEDULE

| | |
|-------------------|---------------------|
| CEILING | R - 39 |
| 2x6 EXTERIOR WALL | R - 24 |
| TKV VALVE | PROVIDED |
| GLAZING | DUAL PAIN / LOW - E |
| DUCTS | R=6 |
| RADIANT BARRIER | NONE |

REQUIRED HERS VERIFICATION

| | |
|---|---|
| <input checked="" type="checkbox"/> DUCT SEALING | <input type="checkbox"/> REFRIGERANT CHARGE TEST |
| <input checked="" type="checkbox"/> IAQ MECHANICAL VENTILATION | <input type="checkbox"/> BLOWER DOOR (2.0 SLA) |
| <input checked="" type="checkbox"/> VERIFIED EER | <input checked="" type="checkbox"/> QUALITY INSULATION INSPECTION |
| <input checked="" type="checkbox"/> VERIFIED SEER | <input type="checkbox"/> THERMAL BYPASS CHECKLIST |
| <input checked="" type="checkbox"/> FAN EFFICIENCY WATTS/CFM | |
| <input checked="" type="checkbox"/> LOW LEAKAGE AIR HANDLING UNIT | |

GRAB BAR REINFORCEMENT FOR BATHROOMS
(USE 2x6 WD STUDS, TYP.)

| | |
|----------------|---|
| WATER CLOSETS: | MOUNTING HTS.: 32" A.F.F. MAX. 36" A.F.F. MIN. BACK OF W/C: 40" WIDE, MIN. SIDE OF W/C: 12" MAX. FROM WALLS, 42" MIN. IN LENGTHS |
| BATHTUBS: | MOUNTING HTS.: 32" A.F.F. MAX. 36" A.F.F. MIN. BACK WALL OF BATHTUB (WIDE SIDE): 12" WIDE FROM EA. SIDE OF WALL, 48" LENGTH MIN. * SIDE WALLS: 6" MAX. FROM BACK WALL, 24" LENGTHS MIN. |
| SHOWERS: | MOUNTING HTS.: 32" A.F.F. MAX. 6" WIDE REINFORCING MIN. TYP. ALL SIDED |

* ADDITIONAL REINFORCING TO BE ADDED TO AREA BETWEEN BATHTUB TOP AND +32" A.F.F.

| AREA | SQ.FT. |
|--------------|--------|
| GROSS | 3,327 |
| LIVING TOTAL | 2,452 |
| 2 CAR GARAGE | 533 |
| PORCH | 157 |
| PATIO | 185 |

KEY NOTES

| | |
|----|---|
| 1 | ONE HOUR 5/8" TYPE "X" GYPSUM BOARD AT WALLS AND CEILING OF GARAGE ONLY. WRAP ALL BEAMS, SHEETROCK AND TAPE ONLY. |
| 2 | ONE SHELF AND ONE POLE |
| 3 | BUILT IN 24" DEEP BASE CABINETS |
| 4 | BUILT IN 12" DEEP UPPER CABINETS |
| 5 | (5) SHELVES EQUALLY SPACED |
| 6 | 36" HOOD VENT W/ 100 CFM AIR EXCHANGE MIN. |
| 7 | ONE SHELF AND 2 POLES |
| 8 | PROVIDE LOW FLOW WATER CLOSETS, MAX. 1.6 GALLONS PER FLUSH WITH EXHAUST FAN ABV. |
| 9 | SOFFIT SEE EXTERIOR ELEVATIONS |
| 10 | SHOWER (36"x72") WITH TILE TO 7'-0" MIN. WITH TEMPERED FIBERGLASS ENCLOSURE |
| 11 | DRYER SPACE WITH EXHAUST FAN ABOVE |
| 12 | WASHER SPACE |
| 13 | SINK WITH DISPOSAL |
| 14 | ADD INSULATION AT POWDER BATH / WATER CLOSET FOR SOUND BARRIER |
| 15 | 36" GAS COOKTOP W/BUILT IN CABINETS BELOW |
| 16 | 30"x30" ATTIC ACCESS FOR MECHANICAL UNIT SHALL BE WEATHER-STRIPPED AND INSULATED TO THE EQUIVALENT OF THE CEILING INSULATION |
| 17 | FULL HEIGHT BUILT IN LINEN CABINET |
| 18 | 36" MINIMUM REFRIGERATOR SPACE |
| 19 | TANKLESS ELECTERICAL WATER HEATER REFER TO MECHANICAL DRAWINGS |
| 20 | DRYER DUCT VENTED THROUGH ROOF |
| 21 | CONDENSING UNIT LOCATION ON CONCRETE PAD - EXTENDING 3' ABOVE ADJOINING GRADE |
| 22 | CONCRETE SLAB |
| 23 | DOOR LANDINGS @ EGRESS DOOR SHALL NOT BE MORE THAN 1 1/2" LOWER THAN THE TOP OF THE THRESHOLD. NOT MORE THAN 7 3/4" PROVIDED THAT THE DOOR DOES NOT SWING OVER THE LANDING OR FLOOR. (PER CBC R311.3.1) |
| 24 | SOFFIT AT TOP OF GARAGE SEE EXTERIOR ELEVATIONS |
| 25 | BATHROOM WALLS TO HAVE SOUND INSULATION |
| 26 | GRAB-BAR REINFORCEMENT: 2x6 BLOOMING +42" |
| 27 | STEPPED ENTRY |
| 28 | ZERO STEP ENTRY |
| 29 | UTILITY SINK (INSTALL PER MANUF. SPECS.) |
| 30 | SOFFIT SEE DETAILS |
| 31 | METAL GATED DOOR SEE EXTERIOR ELEVATION DETAIL |
| 32 | PONY CMU WALL WITH WROUGHT IRON FENCE SEE EXTERIOR DETAIL |

ROOM FINISHES

| ROOM | HEIGHT | FLOOR | WALLS | CEILING |
|---|-----------|----------|--------------------------|--|
| LIVING ROOM, BEDROOMS, CLOSETS, WIC | 10'-0" | CARPET | | |
| HALLWAYS, DINING, . | | | SHEET ROCK | SHEET ROCK |
| BATHROOMS, LAUNDRY, ENTRY, KITCHEN, OWNERS BATH, MUD ROOM | 10'-0" | TILE | | |
| GARAGES | 10'-0" | CONCRETE | 5/8" TYPE "X" SHEET ROCK | 5/8" TYPE "X" SHEET ROCK |
| PORCH, PATIO | VARIABLES | CONCRETE | STUCCO | STUCCO 2x4 HIGH RIB EXPANDED MET. LATH |

WALL LEGEND

| STUDS | TOP PLATE | SILL PLATE |
|---|------------|----------------------|
| EXTERIOR 2x6 @ 24" O.C. - INSULATED | DOUBLE 2x6 | PRESSURE TREATED 2x6 |
| EXTERIOR 2x6 @ 24" O.C. - NON-INSULATED | DOUBLE 2x6 | PRESSURE TREATED 2x6 |
| EXTERIOR WALL W/ STONE SIDING 2x @ 16" O.C. | DOUBLE 2x6 | PRESSURE TREATED 2x6 |
| INTERIOR 2x6 @ 16" O.C. | DOUBLE 2x6 | PRESSURE TREATED 2x6 |
| INTERIOR 2x4 @ 16" O.C. | DOUBLE 2x4 | PRESSURE TREATED 2x4 |

ALL FRAMING GRADED DF#2 OR FINGER JOINTED (GRADE STAMPED BY APPROVED ICBO INSPECTION AGENCY) STUDS DF#2, 10" MAX. MAXIMUM N/A.C.

WINDOW SCHEDULE

| MARK | WIDTH | HEIGHT | AREA,sf | TYPE | MATERIAL | NOTES |
|------|-------|--------|---------|------|----------|-------|
| 1 | 3'-0" | 5'-0" | 15.0 | SH | | |
| 2 | 5'-0" | 5'-0" | 25.0 | XO | | |
| 3 | 4'-0" | 5'-6" | 22.0 | XO | | |
| 4 | 9'-0" | 8'-0" | 96.0 | SLD | TEMP. | |
| 5 | 3'-0" | 6'-0" | 18.0 | SH | | |
| 6 | 2'-0" | 2'-0" | 4.0 | PW | | |
| 7 | 2'-0" | 3'-0" | 6.0 | SH | | |

* PROVIDE TEMPERED GLASS ON ALL WINDOWS FACING GOLF COURSE.

DOOR SCHEDULE

| MARK | WIDTH | HEIGHT | TYPE | MATERIAL | RATING | NOTES |
|------|--------|--------|---------|-------------------|--------|---|
| 1 | 3'-0" | 8'-0" | SWING | FIBERGLASS | | ENTRY DOOR |
| 2 | 3'-0" | 8'-0" | SWING | METAL | | |
| 3 | 3'-0" | 8'-0" | SWING | 1 3/8" SOLID WOOD | | SELF CLOSER & SELF LATCHING SOLID CORE DOOR SHALL PREVENT MIGRATION OF CONTAMINANTS |
| 4 | 2'-10" | 8'-0" | SWING | | | |
| 5 | 9'-0" | 8'-0" | ROLL-UP | METAL | | 1-CAR GARAGE DOOR |
| 6 | 5'-0" | 8'-0" | BYPASS | SOLID WOOD | | |
| 7 | 6'-0" | 8'-0" | BYPASS | SOLID WOOD | | |

*MINIMUM CLEAR HEIGHT OF EGRESS DOOR OPENING SHALL NOT BE LESS THAN 78"



PHONE: (949) 299 7261
Email: info@conceptrender.com

THIS IS AN ORIGINAL UNPUBLISHED WORK AND MAY NOT BE REPRODUCED, DUPLICATED, PUBLISHED OR OTHERWISE USED IN WHOLE OR PART WITHOUT CONSENT OF CONCEPT DESIGN GROUP

RESIDENTIAL DUPLEXES
728 W. VASSAR AVE.
FRESNO CA

FLOOR PLAN

Revisions

Project #:
Date:
Drawn :
Checked:

Sheet Number

A2.0



ELEVATION KEYNOTE

| | |
|---|---|
| ① | SHINGLE ROOF @PLYWOOD PER STRUCTURAL PANEL SCHEDULE - (REFER TO SFT AD-2 FOR MISC. ROOF DETAILS) |
| ② | TYPICAL STUCCO "EAGLE" STUCCO SYSTEM (ESR-2772) OF 1" WRE- MESH & FOAM BOARD; "INSULFOAM" (ESR-1788) OR "FALCON" (ESR-1962) @ 2"-LAYERS OF 60 MIN. GRADE "D" PAPER |
| ③ | GABLE END ATTIC VENT - SEE FRAMING PLAN FOR SIZING |
| ④ | 3 1/2" x 1/2" TYPE WEEP SCREED ATTACHMENT FLANGE, TYP. SEE DETAIL 2B3.7AD-3 |
| ⑤ | PROVIDE 1'-4" OVERHANG UNLESS OTHERWISE NOTED |
| ⑥ | 2x6 FASCIA |
| ⑦ | PROVIDE G.I. SHEET METAL FLASHING AND COUNTER FLASHING AS REQUIRED |
| ⑧ | LIGHT FIXTURE - SEE ELECTRICAL DWGS. |
| ⑨ | CONDENSING UNIT LOCATION ON CONC. PAD |
| ⑩ | BUILDING SHALL HAVE APPROVED ADDRESS NUMBERS PLACED IN A POSITION THAT IS LEGIBLE FROM THE STREET OR ROAD FRONTING THE PROPERTY. (CITY R319-1) A NUMBERS SHALL CONTRAST WITH THEIR BACKGROUND AND BE LEGIBLE. B NUMBERS SHALL BE A MINIMUM OF 4 INCHES HIGH AND A MINIMUM STROKE WIDTH OF 1/32" |
| ⑪ | SIDING/ STUCCO WITH GROOMING LINES |
| ⑫ | STUCCO OVER FOAM TRIM - SEE 7/AD-3 |
| ⑬ | STUCCO OVER FOAM TRIM AT GARAGE - SEE 12/AD-3 |
| ⑭ | PIPE VENT COVER |
| ⑮ | 6X6 POST COVERED BY FYPON COLUMN WRAP |
| ⑯ | PRECAST CONCRETE WALL CAP. SEE DETAIL 16-AD-3 |
| ⑰ | CONCRETE BLOCK WALL |
| ⑱ | WROUGHT IRON FENCE SEE DETAIL 17-AD-3 |
| ⑲ | WROUGHT IRON FENCE SEE DETAIL 18-AD-3 |



CONCEPT
DESIGNGROUP

il: info@conceptrender.com

THIS IS AN ORIGINAL UNPUBLISHED WORK
AND MAY NOT BE REPRODUCED, DUPLICATED
PUBLISHED OR OTHERWISE USED IN WHOLE
OR PART WITHOUT CONSENT OF
CONCEPT DESIGN GROUP

RESIDENTIAL DUPLEXES
728 W. VASSAR AVE.
FRESNO CA

ELEVATIONS

Revisions

| |
|------------|
| Project #: |
| Date: |
| Drawn : |
| Checked: |

Sheet Number

A3.0

WATER EFFICIENCY LANDSCAPE ORDINANCE

Prescriptive Method Notes

Project Info:

Project Applicant: Landscape Connection, INC. (Landscape Designer, Hope Fite)
Phone: (559) 323-8139 Email: hope@landscapeconnection.com
Project: 728 W. Vasser Ave. Fresno, Ca. 93704
Total Landscape Area: 2,577
Bark Area: 1,815
Turf Area: 762 SF
Project Type: New, Non-Residential
Water Supply: Potable

Planter Areas:

(A) For residential areas, install climate adapted plants that require occasional, little, or no summer water (average WUCOLS plant factor 0.3) for 75% of the plant area excluding edibles and areas using recycled water.
(B) A minimum 3" layer of mulch shall be applied on all exposed soil surfaces of planting areas except in turf areas, creeping or rooting groundcovers, or direct seeding applications where mulch is contraindicated.
(C) Compost at a rate of a minimum of four cubic yards per 1,000 square feet of permeable area to a depth of six inches into the soil. Soils with greater than 6% organic matter in the top six inches of soil are exempt from adding compost and tilling.

Irrigation:

(A) Automatic irrigation controllers are required and must use evapotranspiration or soil moisture sensor data.
(B) Irrigation controllers shall be of a type which does not lose programming data in the event the primary power source is interrupted.
(C) Pressure regulators shall be installed on the irrigation system to ensure the dynamic pressure of the system is within the manufacturer's recommended pressure range.
(D) Manual shut-off valves (such as a gate valve, ball valve, or butterfly valve), shall be installed as close as possible to the point of connection of the water supply.
(E) All irrigation emissions devices must meet the requirements set in the ANSI standard, ASABE/ICC 802-2014. "Landscape Irrigation Sprinkler and Emitter Standard," All sprinkler heads installed in the landscape must document a distribution uniformity low quarter of 0.65 or higher using the protocol defined in ASABE/ICC 802-2014.

"I agree to comply with the WELO Prescriptive Compliance Option."

Hope Fite DATE 7/13/2020

PLANTING SCHEDULE



| SYMBOL | SIZE | BOTANICAL / COMMON NAME | WUCOLS |
|--------|---------|---|----------|
| TREES | | | |
| * | 15 GAL. | LAGERSTROEMIA 'MUSKOGEE' / CRAPE MYRTLE, LAVENDER | LOW |
| ■ | 15 GAL. | MAGNOLIA G. 'ST. MARY' / SOUTHERN MAGNOLIA | MODERATE |

SHRUBS / GROUNDCOVERS

| | | | |
|---|--------|---|----------|
| Ⓐ | 1 GAL. | AGAPANTHUS 'PETER PAN WHITE' / DWARF LILY-OF-THE-NILE | MODERATE |
| Ⓐ | 5 GAL. | LIGUSTRUM TEXANUM / PRIVET | LOW |
| Ⓐ | 5 GAL. | MUHLENBERGIA C. 'WHITE CLOUD' / WHITE CLOUD MUHLY | LOW |
| Ⓐ | 1 GAL. | MYOPORUM P. / PROSTRATE MYOPORUM, WHITE | LOW |
| Ⓐ | 1 GAL. | OLEA E. 'PETITE OLIVE' / OLIVE, SHRUB | VERY LOW |
| ■ | | HYBRID BERMUDA SOD | |

IRRIGATION EQUIPMENT

| SYMBOL | DESCRIPTION - MANUFACTURER - MODEL # |
|--------|--|
| ⊕ | Electric Irrigation Turf Valve - RAIN BIRD - 075-ASVF series (Size as Noted) |
| ⊕ | Electric Irrigation Drip Valve - RAIN BIRD - XACZ-075-PRF series (Size as Noted) |
| Ⓐ | Automatic Irrigation Controllers - RAIN BIRD - ESP-TM2 Indoor w/ WiFi Module |
| ⊗ | Gate Valve - PROFLO -PFT 3006 |
| --- | Pressure Mainline - Sch 40 PVC Pipe |
| --- | RAINBIRD - On-Surface Drip Line - XFD - 06 - 12- 100 |



Landscape Connection

| | | | |
|--|---------------|--|-----------------------|
| LANDSCAPE CONNECTION, INC. LIC.# 935734 6374 E. SHEPHERD AVE. ; CLOVIS, CA 93619 P: (559) 323-8139 F: (559) 323-7057 | | | |
| PROJECT TITLE: RESIDENTIAL DUPLEXES 728 W. VASSER AVE. FRESNO, CA. 93704 | REVISED DATE: | SCALE: AS SHOWN DATE: 7-13-2020 DRAWN BY: HF | PROJECT NO. 20-365 |
| SHEET TITLE: PLANTING PLAN | | | 1 OF 1 |