




**Exhibit I – City of Fresno**  
**Public Works Department Standard P-21**  
**(Parking Lot Paving Details)**



TYPICAL CROSS SECTIONS



OPTIONAL—WITH APPROVED TEST

NOTES:

1. SURFACE DRAINAGE SHALL BE TO STREET.
2. PARKING BUMPERS TO BE PLACED SO THAT PARKED CARS WILL NOT OVERHANG ON SIDEWALKS OR STREETS.
3. THE OPTIONAL CROSS-SECTION MAY BE USED UPON SUBMISSION OF "R" VALUE TESTS TAKEN BY AN APPROVED LABORATORY SUBSTANTIATING THE USE OF EXISTING SOIL FOR THE BASE. A MINIMUM VALUE OF 65 WILL BE REQUIRED.
4. WHERE ASPHALT CONCRETE IS APPLIED TO THE NATIVE SOIL, SOIL STERILANT AS PER MANUFACTURERS SPECIFICATIONS WILL BE REQUIRED BEFORE THE SURFACE MATERIAL IS PLACED. WEED KILLER TO BE APPLIED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATION.
5. SURFACE DRAINAGE TO ALLEY ONLY BY WRITTEN APPROVAL OF THE CITY ENGINEER.
6. TEMPORARY PARKING LOTS (USE NOT TO EXCEED 60 DAYS) SHALL BE GRADED AND ROLLED SMOOTH. THE TOP 6" OF NATIVE SOIL SHALL BE COMPACTED TO 85% RELATIVE COMPACTION USING TEST METHOD ASTM 1557. A DUST PALLIATIVE PER STATE STANDARD SPECIFICATIONS AT THE RATE OF 1 GAL./SQ. YD. TO OBTAIN A MINIMUM PENETRATION OF 1". THE MIXING RATIO SHALL BE 4:1 PER STATE STANDARD SPECIFICATIONS. THE DEVELOPER SHALL POST A BOND TO GUARANTEE REMOVAL OF ALL IMPROVEMENTS FOR A TEMPORARY PARKING LOT.